



# WINDOW PRODUCTS LIMITED

Effective solutions for windows manufacturers and fitters

Unit 4203 Oakfield Close,  
Tewkesbury Business Park,  
Tewkesbury, Glos  
GL20 8PF


T: 01684 290944

E: sales@gtwindowproducts.co.uk


W: www.gtwindowproducts.co.uk

## GT Sash Seal


Patent No. GB2458736B



Fit a Sash Spring to the sash on the center line of the stay fixing area



Fit a 17mm Frame Wedge to the outer frame on the stay fixing area



It may be necessary to pack the sash/glass at this point as shown

All drawings are not to scale  
Reinforcement and fixings have been omitted for clarity

**GT SASH SEAL** is a spring device designed to improve the seal of a sash at the hinged side of a window.

It consists of 1 acetal moulding and 1 spring steel component designed to universally fit all 13mm and 17mm stack height systems.

The simple act of closing the window causes the unique Sash Spring to push against the Frame Wedge to ensure an efficient seal

**Universal** - fits any window that uses standard stays

**Universal** - accommodates almost all the current easy-clean and egress stays available

**Universal** - solution for Aluminium, PVCu, and Timber frames

**Universal** - one spring steel component with either 13mm or 17mm acetal wedge

**Benefit** - saves call out costs to leaking casement windows

**Benefit** - one component fits all

Locate the components on the stay fixing area as shown in both diagrams.

This position is a universal fixing point and will enable the **Sash Seal** to be used on all PVCu, Aluminum, and Timber frames.

One **Sash Seal** set will give adequate seal if fix centrally on the hinge stile.

### Part Numbers

- SS001 Sash Spring Standard
- SS002 White Wedge 13mm
- SS003 Black Wedge 13mm
- SS008 Brown Wedge 13mm
- SS009 Tan Wedge 13mm
- SS004 White Wedge 17mm
- SS005 Black Wedge 17mm
- SS006 Brown Wedge 17mm
- SS007 Tan Wedge 17mm
- SS100 Sash Spring Long